



GTWY2000

GTWY6-2000 / GTWY8-2000 / GTWY10-2000 / GTWY12-2000


S.W.L	GTWY6-2000/GTWY8-2000	GTWY10-2000	GTWY12-2000
	300 kg	250 kg	200 kg

Working height	GTWY6-2000	GTWY8-2000	GTWY10-2000	GTWY12-2000
	8.00m	10.00m	12.00m	14.00m
Platform floor height	GTWY6-2000	GTWY8-2000	GTWY10-2000	GTWY12-2000
	6.00m	8.00m	10.00m	12.00m

Overall length	GTWY6-2000/GTWY8-2000	GTWY10-2000	GTWY12-2000
	1.56m	1.79m	1.84m
Overall width	GTWY6-2000/GTWY8-2000 /GTWY10-2000	GTWY12-2000	
	0.84m	0.89m	
Overall height	GTWY6-2000/GTWY8-2000 /GTWY10-2000	GTWY12-2000	
	1.86m	2.08m	
Platform size	GTWY6-2000/GTWY8-2000	GTWY10-2000/GTWY12-2000	
	1.21X 0.6m	1.45X 0.6m	
Ground clearance	0.08m		
Wheelbase	GTWY6-2000/GTWY8-2000	GTWY10-2000/GTWY12-2000	
	1.17m	1.42m	

Lifting motor	AC	DC
	110-230VAC/1.5kw	12VDC/2.5kw

Up/Down speed	GTWY6-2000	GTWY8-2000	GTWY10-2000	GTWY12-2000
	58/40 sec	62/43 sec	70/46 sec	75/54 sec



Batteries	2X12V/150Ah
Integrated charger	12 V/15A

Tyres	
Back wheels	φ200X50mm
Front wheels	φ180X50mm

Weight	GTWY6-2000	GTWY8-2000	GTWY10-2000	GTWY12-2000
	570(AC)/610(DC) kg	630(AC)/670(DC) kg	730(AC)/770(DC) kg	825(AC)/865(DC) kg

Standard equipment

- Leveling outrigger device
- Emergency stop button
- Battery charge indicator
- Electric limit switch
- Two controllers operation
- Emergency down button
- Leveling indicator
- Over loading limited

GTWY6-2000	8m	GTWY6-2000	8m
GTWY8-2000	10m	GTWY8-2000	8m
GTWY10-2000	12m	GTWY10-2000	10m
GTWY12-2000	14m	GTWY12-2000	12m

